



# PORTABLE HOT WATER PRESSURE WASHER

**DIRECT DRIVE / ELECTRIC DRIVEN / DIESEL FIRED**



**Adjustable thermostat**  
up to 89°C/193°F with illuminated  
rocker switch and hour meter

**American made**  
heavy-duty 6,000 PSI  
rupture disk

**Heavy-duty roll-cage powder  
coated 1.5" OD steel tube**  
frame, with centre balanced  
lift hook (above industry standards)

**Lifting hook**

**2.0 HP TechTop Motor**  
120V 20A Nema  
5-20P Plug

**Heating Coil**  
1/2" Heavy-duty schedule 80  
American made Carbon  
Steel Cold-rolled pipe

**80' length coil** for maximum  
heat rise and proper heat  
production, 5,500PSI rated

**Direct Drive AR  
Triplex pump** carries  
a 5-year warranty

**Dual Brake assembly**  
safely secures unit  
in place

**Stainless-steel coil  
skin** provides extra  
durability and  
resists corrosion


**22 L / 6 gal** removable,  
rust-proof polyethylene  
diesel fuel tank

**12" heavy-duty**  
flat free tires

**120V Wayne burner**  
ignites diesel to  
heat water

**3/4" HD Threaded**  
mount axle

**TMR** TRUCK  
MOUNT  
READY  
Mounting bracket



**360° Hose reel**  
swivel bracket  
(sold separately: 59.400.001)

## FEATURES

- 36" gun wand assembly with insulated grip and quick connect
- 50' x 3/8" twin wire braided hose
- Adjustable low-pressure chemical injector assembly with quick connects
- 4 color-coded quick connect spray nozzles
- 1 color-coded quick connect chemical nozzle

## WARRANTY

MOTOR ..... 2 YEARS  
 PUMP ..... 5 YEARS  
 ACCESSORIES... 90 DAYS  
 FRAME ..... LIFETIME  
 COIL ..... 3 YEARS

MODEL # HW152EA



## DIRECT DRIVE

MODEL	GPM	PSI	HP	MOTOR	BTU/HR	PUMP MODEL	DRIVE	BURNER FUEL CONSUMPTION	UNIT DIMENSIONS	SHIPPING DIMENSIONS	SHIP WT (lbs)
HW152EA	2.0	1,500	2.0	TECHTOP	172,000	AR JRV2G25E	DIRECT	1.32 GPH	42"L x 27"W x 43"H	37"L x 30"W x 49"H	388



# PORTABLE HOT WATER PRESSURE WASHER ACCESSORY OPTIONS

85.610.804

## ACCESSORY OPTIONS

<b>500195</b>	HOSE REEL - 360° PIVOT, 150' MAX LENGTH, 300° F (STEAM RATED SWIVEL) COMES WITH WHIP HOSE
<b>59.400.001</b>	360° HOSE REEL SWIVEL BRACKET
<b>85.205.090</b>	SPRAY GUN WITH DUAL WAND TO SWITCH FROM PRESSURE TO SOAPER BARREL
<b>85.210.135</b>	ROTARY NOZZLE #3.5, SPRAYS IN A CIRCULAR PATTERN, 5,000 PSI
<b>85.490.016</b>	SOOT REMOVER, 125 ML (4 OZ)
<b>59.400.004</b>	7" RAIN CAP / EXHAUST CHIMNEY

## HOSE REEL FEATURES

- **Hose Capacity:** 150' x 3/8"
- **Hose Axle:** Stops hose from kinking when attached to hose reel axle. Eliminates wear on hose, for longer life
- **Adjustable Friction Brake:** Eliminates hose backlash when unwinding
- **Heavy-Duty Performance:** Super Swivel rated to 5,000 PSI & 300°F standard
- **Easy Push / Pull Spring Loaded Lock Pin:** Prevents unwanted hose unwinding
- **Multi-Position Collar with Spring Loaded Lock Pin:** Allows reel to be positioned in a variety of positions and locked
- **Durable Construction:** Heavy gauge cold rolled metal. Durable reel, capable of securely storing high pressure hose.
- **Easy Turn Handle:** Prevents fatigue when coiling your hose
- **Hose Guide -** Allows for easy hose rolling & prevents tangling
- **Double Bearing Design with Stainless Steel Shaft:** Prevents side movement and allows reel to swivel freely
- **Locking Collar Shaft:** Prevents reel from sliding out of the bracket vertically
- **Smooth Radius Bent Arm:** Eliminates 90° bend and strengthens the arm



500195

SWIVEL REEL



85.210.135



59.400.004



59.400.001



85.205.090



85.490.016