

## 1,500 PSI - 2.0 GPM HOT WATER PRESSURE WASHER WITH TECHTOP MOTOR AND AR TRIPLEX PUMP

COMMERCIAL SERIES

MODEL: HW152EA

### FEATURES

- **2.0 HP TECHTOP motor** delivers energy efficiency and reliability suited for commercial applications.
- **Direct drive** system connects the engine to the pump for a compact and efficient power transfer.
- **Commercial grade AR triplex pump** featuring die-cast body, forged brass manifold, ceramic coated plungers and thermal release valve.
- **Built-in unloader** effectively regulates water flow in a compact design.
- **The diesel fueled burner** can be turned on or off and the thermostat can heat water up 89°/193°F with an output of 172,000 BTU.
- **Heating coil** has a stainless steel wrap protecting the heavy duty 1/2" schedule 80 carbon steel cold rolled pipe.
- **Commercial grade accessories** included are a 50 foot high-pressure hose, spray gun wand assembly, and five spray nozzles.
- **Powder coated steel frame** with four 12" tires for stability and to handle rough terrain. Roll cage design protects the components while allowing easy access to use or maintain.
- **A lift point** is built into the frame to allow the use of a crane to lift it onto a truck or trailer.



Scan the QR code with your mobile device and discover more about this BE Pressure washer.

PLUG TYPE



GFCI - NEMA 5-20P

### MOTOR

MODEL: **TECHTOP**  
 HORSEPOWER: **2.0**  
 AMPS: **20**  
 VOLTS: **120, SINGLE PHASE**  
 PLUG TYPE: **NEMA 5-20**  
 CORD LENGTH: **25'**

### PUMP SPECS

TYPE: **AR JRV2G25E**  
 PART NUMBER: **85.129.083H**  
 OIL TYPE: **30W NON-DETERGENT**  
 SOAP SYSTEM: **FIXED INJECTOR**

### UNLOADER

TYPE: **BUILT IN**  
 PART NUMBER: **AR43988**

### BURNER

IGNITER: **WAYNE 120V**  
 THERMOSTAT: **0° TO 89°C/193°F**  
 BTU: **172,000**  
 HEATING COIL: **1/2" COLD ROLLED STEEL**  
 FUEL CAPACITY: **6 GALLON**  
 FUEL TYPE: **DIESEL/KEROSENE**  
 FUEL CONSUMPTION: **1.32 GPH**

### ACCESSORIES

HOSE TYPE: **50' X 3/8" TWIN WIRE BRAIDED**  
 PART NUMBER: **85.238.251**  
 NOZZLES: **0°, 15°, 25°, 40° AND SOAPER**  
 PART NUMBER: **85.210.035BEP**  
 GUN WAND: **36" INSULATED**  
 PART NUMBER: **85.205.026**  
 FITTINGS: **QUICK CONNECT**

### FRAME

MATERIAL: **POWDER COATED**  
 WHEELS: **12" FLAT FREE**

### SHIPPING SIZE

LxWxH: **37" x 30" x 49"**  
 WEIGHT: **388 LBS**

### UNIT SIZE

LxWxH: **42" x 27" x 43"**  
 WEIGHT: **320 LBS**

### WARRANTY

MOTOR: **2 YEARS**  
 PUMP: **5 YEARS**  
 COIL: **3 YEARS**  
 UPC: **777987342873**

02-2023

## LAVEUSE À PRESSION EAU CHAUDE 1,500 PSI - 2.0 GPM AVEC MOTEUR TECHTOP & POMPE AR TRIPLEX

COMMERCIAL

SERIES

MODÈLE: HW152EA

### CARACTÉRISTIQUES

- **Moteur TechTop 2.0 HP**, fournissant efficacement et fiabilité l'énergie adaptées aux applications commerciales.
- **Système d'entraînement** direct connecte le moteur à la pompe pour un transfert de puissance compacte et efficace.
- **Pompe grade Commercial AR triplex** ayant un corps moulé, collecteur laiton forgé, pistons en céramique et soupape de décharge thermique.
- **Déchargeur intégré** régularise efficacement le débit d'eau dans une conception compacte.
- **Le brûleur peut être arrêté** et contrôlé avec un thermostat ajustable pouvant être configuré jusqu'à 89°/193°F.
- **La bobine de chauffage** est allumée par un brûleur 120v Wayne alimenté au diesel.
- **Accessoires grade Commercial** incluant boyau haute pression 50', ensemble lance et pistolet et quatre buses.
- **Cadre en acier thermolaqué** avec rangement pour accessoires, quatre pneus à toute épreuve 12" maximisant la stabilité et capacité à traverser des terrains difficiles.
- **Un point de levage est** intégré au châssis permettant l'utilisation d'une grue pour le soulever sur un camion ou remorque.



Scannez le code QR avec votre cellulaire et apprenez-en plus à propos de cette laveuse BE Pressure.

TYPE DE PRISE



GFCI - NEMA 5-20P

### MOTEUR

MODÈLE: **TECHTOP**  
PUISSANCE EN CHEVAUX: **2.0**  
AMPÉRAGE: **20**  
VOLTS: **120, UNIQUE PHASE**  
TYPE DE PRISE: **NEMA 5-20**  
LONGUEUR DU CORDON: **25'**

### BRÛLEUR

IGNITER: **WAYNE 120V**  
THERMOSTAT: **0° TO 89°C/193° F**  
BTU: **172,000**  
BOBINE DE CHAUFFAGE: **ACIER LAMINÉ À FROID 1/2"**  
CAPACITÉ D'ESSENCE: **6 GALLON**  
TYPE D'ESSENCE: **DIESEL/KEROSENE**

### CHÂSSIS

MATÉRIEL: **ACIER THERMOLAQUÉ**  
ROUES: **À TOUTE ÉPREUVE 10"**

### TAILLE D'EXPÉDITION

LxWxH: **37" x 30" x 49"**  
POIDS: **388 LBS**

### SPÉCS POMPE

TYPE: **AR JRV2G25E**  
NUMÉRO PIÈCE: **85.129.083H**  
TYPE D'HUILE: **30W NON-DETERGENT**  
SYSTÈME DE SAVON: **INJECTEUR FIXE**

### ACCESSOIRES

TYPE DE BOYAU: **DOUBLE FIL TRESSÉ 50' X 3/8"**  
NUMÉRO PIÈCE: **85.238.251**  
BUSES: **0°, 15°, 25°, 40° ET À SAVON**  
NUMÉRO PIÈCE: **85.210.035BEP**  
PISTOLET LANCE: **ISOLÉE 36"**  
NUMÉRO PIÈCE: **85.205.026**  
RACCORDS: **CONNECTION RAPIDE**

### TAILLE DE LA BOÎTE

LxWxH: **42" x 27" x 43"**  
POIDS: **320 LBS**

### DÉCHARGEUR

TYPE: **INTÉGRÉ**  
PIÈCE: **AR43988**

### GARANTIE

MOTEUR: **2 YEARS**  
POMPE: **5 YEARS**  
BOBINE: **3 YEARS**  
UPC: **777987342873**

02-2023